



## Main Features

- › Full-Automatic Operation
- › Double-Layered Chassis with 4 mm-Thick Metal Plate and Low Center of Gravity Provides Stable Playback
- › Built-in Phono Equalizer with On/Through Selector: On for Connecting Amps without Phono Terminal, Through When Using External Phono Equalizer
- › High-Performance MM Cartridge Included
- › Original 5 mm-Thick Rubber Mat Suppresses External Vibration While Firmly Gripping the Record
- › Aluminum Die-Cast Platter
- › Aluminum Die-Cast Tone Arm
- › Aluminum Die-Cast Exchangeable Headshell
- › Anti-Skating Dial for Accurate Tracking
- › Speed Selector
- › Size Selector
- › Gold-Plated Pin Plug
- › Detachable Power Cord
- › Unobtrusive Design Matches Any Décor

## Included Accessories

- › Turntable
- › Turntable Sheet
- › Dust Cover with Removable Hinges
- › Adapter for EP Record
- › Balance Weight
- › Headshell with Cartridge
- › Spare Lead Wires
- › Power Cord
- › Operating Instructions

## Main Specifications

- › Power Requirements: AC 120 V, 60 Hz
- › Power Consumption: 2 W
- › Output: RCA (Stereo Pin Plugs) x 1
- › Maximum Dimensions (W x H x D): 17-3/16" x 4-6/16" x 14-11/16" (435 x 110 x 372.6 mm)
- › Main Unit Weight: 12.3 lb. (5.6 kg)

## Turntable SPECIFICATIONS

- › Drive Method: Belt Drive System
- › Wow and Flutter: 0.1% or Less WRMS (JIS WTD)
- › Motor: DC Servo Motor
- › S/N Ratio: 60 dB (DIN-B)
- › Rotation Speed: 33 1/3 rpm, 45 rpm

## Tone Arm SPECIFICATIONS

- › Arm Type: Static Balance Straight Type Tone Arm
- › Effective Length: 221.5 mm
- › Overhang: 19 mm
- › Stylus Pressure Variable Range: 0 g to 4.0 g (1 scale 0.1 g)
- › Proper Cartridge Weight: 4.5 g to 9.5 g (Single Cartridge)
- › Cartridge Type: MM Type
- › Headshell Weight: 10.0 g (Including Screws and Nuts)